







4	FOOT END EQUIPMENT ELEVATION
	NOT TO SCALE

EQUIPMENT LIST					
TAG	QTY	DESCRIPTION			
B1	1	A Series-Accessory Arm(s), Surgical Light(s) & Accessory Arm(s)			
C1	1	Tandem HarmonyAlR Adj Arm Monitor Carrier - HarmonyAlR Fixed-Equipment, Monitor Carrier			
C2	1	HarmonyAIR Adj Arm, Motor Supply Head-Anesthesia			
C3	1	Tandem HarmonyAIR Fixed - A Series-Perfusionist, Surgical Light(s) & Accessory Arm(s)			
K1	1	HarmonyAIR A-Series Integrated Wall Control			

A SERIES LIGHT CONDUIT SCHEDULE						
FROM - TO	QUANTITY SIZE RESPONSIBIL		responsibility			
K1 - B1	2	.75"	ELECTRICAL CONTRACTOR			
K1 - B2	1	.75"	ELECTRICAL CONTRACTOR			
B1 - B2	CONNECTED VIA FLEX CONDUIT INCLUDED IN SPLIT MOUNT KIT					
LICHT CONDITIT SCHEDLILE NOTES						

- LIGHT CONDUIT SCHEDULE NOTES

 1. 5" CONDUIT FOR AC POWER TO K1; 3 COND. 10AWG WIRE INPUT AC SUPPLY 120V-240VAC, 7A-3A, 50/60Hz

 2. LIGHTING CONDUIT RUNS NOT TO EXCEED 25 FEET

 3. CONDUIT REQUIREMENTS FOR LIGHTS ALSO REFERENCED WITHIN THE EQUIPMENT DRAWINGS FOR THE SPECIFIED SURGICAL LIGHT WALL CONTROL SYSTEM

 4. DC SUPPLY LIGHTHEAD CABLES REQUIRE 1" CONDUIT WHEN DOUBLE RUNS ARE REQUIRED (LONG RUNS)

 5. REFER TO APPROPRIATE EQUIPMENT SPECIFICATIONS TO ENSURE THAT THE MOST CURRENT & DETAILED INFORMATION OF THIS LIGHT SYSTEM IS UTILIZED

THIS LAYOUT IS INTENDED TO ENCOURAGE DISCUSSIONS FOR AN INTEGRATED DESIGN PROCESS.
FOR AN OPTIMIZED OPERATING ROOM DESIGN SOLUTION, PLEASE CONTACT YOUR LOCAL STERIS REPRESENTATIVE.
REFER TO THE IMAGING VENDOR FOR ALL IMAGING SYSTEM DIMENSIONS, LOCATIONS, AND REQUIREMENTS.



HYBRID OPERATING ROOM PROPOSED EQUIPMENT LAYOUT HYBRID DESIGN TEMPLATE CANON - ALPHENIX SKY+

			TE	MPL	ATE
DR	CD	CK	MEJ	DATE	01MAR2023
SCALE	NC	OT TO	SCALE	PAGE	01