



114" CEILING HEIGHT	 B2	60"	102"
	FOOT E	nd equipment el	LEVATION NOT TO SCALE

55" MAXIMUM 23" MINIMUM	
FOOT END EQUIPMENT ELEVATION NOT TO SCALE	

EQUIPMENT LIST			
TAG	QTY	DESCRIPTION	
B1	1	A Series-Surgical Light(s) & Accessory Arm(s)	
B2	1	A Series-Accessory Arm(s), Surgical Light(s) & Accessory Arm(s)	
C1	1	Tandem HarmonyAIR Adj Arm Monitor Carrier - HarmonyAIR Fixed-Equipment, Monitor Carrier	
C2	1	HarmonyAIR Adj Arm, Motor Supply Head-Anesthesia	
K1	1	HarmonyAIR A-Series Integrated Wall Control	

A SERIES LIGHT CONDUIT SCHEDULE			
FROM - TO	QUANTITY	SIZE	RESPONSIBILITY
K1 - B1	2	.75"	ELECTRICAL CONTRACTOR
K1 - B2	1	.75"	ELECTRICAL CONTRACTOR
B1 - B2	CONNECTED VIA FLEX CONDUIT INCLUDED IN SPLIT MOUNT KIT		

- LIGHT CONDUIT SCHEDULE NOTES

  1. 5" CONDUIT FOR AC POWER TO K1; 3 COND. 10AWG WIRE INPUT AC SUPPLY
   120V-240VAC, 7A-3A, 50/60Hz
  2. LIGHTING CONDUIT RUNS NOT TO EXCEED 25 FEET
  3. CONDUIT REQUIREMENTS FOR LIGHTS ALSO REFERENCED WITHIN THE
  EQUIPMENT DRAWINGS FOR THE SPECIFIED SURGICAL LIGHT WALL
  CONTROL SYSTEM
  4. DC SUPPLY LIGHTHEAD CABLES REQUIRE 1" CONDUIT WHEN DOUBLE RUNS
  ARE REQUIRED (LONG RUNS)
  5. REFER TO APPROPRIATE EQUIPMENT SPECIFICATIONS TO ENSURE THAT THE
  MOST CURRENT & DETAILED INFORMATION OF THIS LIGHT SYSTEM IS
  UTILIZED

THIS LAYOUT IS INTENDED TO ENCOURAGE DISCUSSIONS FOR AN INTEGRATED DESIGN PROCESS. FOR AN OPTIMIZED OPERATING ROOM DESIGN SOLUTION, PLEASE CONTACT YOUR LOCAL STERIS REPRESENTATIVE. REFER TO THE IMAGING VENDOR FOR ALL IMAGING SYSTEM DIMENSIONS, LOCATIONS, AND REQUIREMENTS.



HYBRID OPERATING ROOM PROPOSED EQUIPMENT LAYOUT HYBRID DESIGN TEMPLATE GE - INNOVA 3100 / IGS 520

			TE	MPL	ATE
DR	CD	CK	MEJ	DATE	01MAR2023
SCALE	NC	OT TO	SCALE	PAGE	01